

CALGAZ

6D NON-REFILLABLE CYLINDER

Contents

103 liters

Service Pressure

1000 psig/69 bar

Dimensions

13 7/8" x 3 1/4"/352mm x 83mm

Weight

3 lb/1.4 kg

Cylinder Material

Steel

Recommended Use

Recommended for use with non-reactive gas mixtures. Gases include, but are not limited to, mixtures containing: Air, Benzene, Butane, Carbon Dioxide, Carbon Monoxide, Hexane, Hydrogen, Isobutylene, Methane, Nitrogen, Oxygen, Pentane, Propane and Toluene.

Recommended Equipment

Model 715, DFR 2000 Series, or Trigger regulators.
Connection is 5/8-18UNF thread.

Mixture Tolerances

Minor components are certified to $\pm 2\%$.

Warranty

Most gas mixtures are warranted for 36 months.

Approvals

The 6D Cylinder meets European Standard EN12205,
U.S. DOT-39, Canadian TC-39M and ISO11118 Specifications.

Note: all mixtures are NIST traceable.



www.calgaz.com

North America

821 Chesapeake Drive
Cambridge, MD 21613
U.S.A.

Phone: +1 800 638 1197

+1 410 228 6400

Fax: +1 410 228 4251

Europe/Africa

Unit 5, Crown Royal Ind. Park
Shawcross Street, Stockport
Cheshire, SK1 3EY

United Kingdom

Phone: +44 161 968 5060

Fax: +44 161 477 0590

Middle East

Suite 829 West Wing 4B
Dubai Airport Free Zone
PO Box 54638, Dubai, U.A.E.

Phone: +971 4 299 3444

Fax: +971 4 299 3668

Additional Worldwide Location
Australia

