

CALGAZ

8AL NON-REFILLABLE CYLINDER

Contents

58 liters

Service Pressure

500 psig/34.5 bar

Dimensions

14 1/4" x 3 1/2"/362 mm x 89 mm

Weight

1.6 lb/0.73 kg

Cylinder Material

Aluminum

Recommended Equipment

Model 715, DFR 2000 Series, or Trigger regulators.

Connection is 5/8-18UNF thread.

Most applications require Teflon® tubing.

Mixture Tolerances

Minor components are certified to the following analytical accuracy:

1 - 20 ppm: ± 10%

21 - 50 ppm: ± 5%

51 ppm and above: ± 2%

Warranty

Non-Reactive Mixtures	36 months
H ₂ S, H ₂ S/CO/LEL/O ₂ /N ₂ , SO ₂ and C ₆ H ₆ Mixtures	24 months
NH ₃ , PH ₃ , NO, and HCN Mixtures	18 months
ETO, SiH ₄ and HCL Mixtures	12 months
CL ₂ Mixtures	9 months
NO ₂ Mixtures	6 months

Approvals

The 8AL Cylinder meets European Standard EN12205, U.S. DOT-39 and Canadian TC-39M Specifications.

Note: All mixtures are N.I.S.T. traceable.

®Registered Trademark of The Dupont Company



www.calgaz.com

North America

821 Chesapeake Drive
Cambridge, MD 21613
U.S.A.

Phone: +1 800 638 1197

+1 410 228 6400

Fax: +1 410 228 4251

Europe/Africa

Unit 5, Crown Royal Ind. Park
Shawcross Street, Stockport
Cheshire, SK1 3EY

United Kingdom

Phone: +44 161 968 5060

Fax: +44 161 477 0590

Middle East

Suite 829 West Wing 4B
Dubai Airport Free Zone
PO Box 54638, Dubai, U.A.E.

Phone: +971 4 299 3444

Fax: +971 4 299 3668



Additional Worldwide Location
Australia